

FillerMix

Wood joint filler

PRODUCT FEATURES

- Waterborne binder for the preparation of wood putty
- Combine with pure sanding dust from the wooden floor on which it will be used
- Use for filling of cracks and joints between wood and parquet panels or squares
- Dries rapidly, has good filling ability and is easy to sand
- Low solvent content, non-flammable and has a neutral odour
- For indoor use only

PREPARATION

Sand the floor down to bare wood. Shake Arboritec Filler Mix well before use. Mix clean sanding dust from the penultimate floor sanding (60- to 80-grit) with Arboritec Filler Mix to form a putty-like mass.

APPLICATION

Apply Arboritec Filler Mix to the entire floor using a spatula. Large joints may require two or three applications. Allow at least 60 minutes drying time depending on air humidity and temperature. For the final sanding use 120-grit.

Arboritec Filler Mix is designed for use together with Arboritec lacquers or floor oils.

CLEANING

Clean spatula and other tools with water.

HEALTH AND ENVIRONMENT

Arboritec Filler Mix is not classified under the C.H.I.P regulations. Normal care necessary for handling of chemical products must be taken. Ensure good ventilation. Use protective glasses and gloves if there is a risk of splashing. In the event of skin contact, wash with soap and water. In the event of contact with eyes, rinse thoroughly with water. For further information see Material Safety Data Sheet.



TECHNICAL DATA

Contents:	Fibre-reinforced acrylate copolymer
Usage:	1litre for ca. 8-10 m ²
Solvents:	<1%
pH.:	7-8
Drying time:	3 to 24 hours to final polishing 10 hours after final polishing
Storage:	Best before 12 months at +10°C to +25°C. in unopened package. Protect from frost. Keep out of the reach of children.
Package:	5 litre plastic containers 1 litre plastic containers

This Arboritec Product Sheet is intended for advice only. The figures apply to normal conditions, which may vary due to means of application, temperature etc. We retain the right to make changes and amendments without prior notice.

A safety data sheet is available for professional users on request. Keep out of the reach of children.

For technical advice: Contact your distributor or Arboritec Technical Service at +46 303 56330

The information and recommendations in this data sheet are guidelines for application and are not to be construed as a guarantee. In all cases it is the responsibility of the user to determine if the product is suitable for the purpose, and complete a successful application. Arboritec can only guarantee the delivered product. If the user is in doubt we would recommend a preliminary onsite test. Please ensure you have read and understood all information on the labels and in the safety data sheets before using this product.

Rev 13-04-25. This data sheet replaces all previous versions.